

1003424


sport

Audi ABC 2nd generation: 7mm valves

V-6cyl 2.6L 12v SOHC (DTH/DTH)



	intake	exhaust
camshaft data:		
lash ramp	: hydro	hydro
duration @ 0.1mm	: 283°	283°
duration @ 1.0mm	: 247°	247°
valve lift	: 11.50mm	11.50mm
cam lift	:	
lobe angle	: 110°	110°
timing @ 1.0mm	: 14° / 53°	54° / 13°
valve lift @ TDC	: 2.70mm	2.70mm
parts setup:		
cam wheels :	:	:
follower	: O.E.M.	: O.E.M.
valve lash	: O.E.M.	: O.E.M.
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: 99386	: 99386
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: PAC-S90019	: PAC-S90019
interior spring	:	:
fitted load / length	: 33kg @ 35.0mm	: 33kg @ 35.0mm
max. load / lift	: 80kg @ 12.0mm	: 80kg @ 12.0mm



REMARKS :

ONLY for dirt track applications and pro street use with adjustable engine management or carburetors

REMARKS :

if required, machine cylinder head and / or use solid shims to adjust spring load

check distance between valve seal and retainer to be at least 0.6mm at full lift