

1003501


hot street - dirt track

Audi ABC 2nd generation: 7mm valves

V-6cyl 2.6L 12v SOHC (DTH/DTH)



	intake	exhaust
camshaft data:		
lash ramp	: 0.30mm	0.30mm
duration @ 0.1mm	: 284°	284°
duration @ 1.0mm	: 244°	244°
valve lift	: 12.00mm	12.00mm
cam lift	:	
lobe angle	: 110°	110°
timing @ 1.0mm	: 12° / 52°	52° / 12°
valve lift @ TDC	: 2.80mm	2.75mm
parts setup:		
cam wheels :	:	:
follower	: CC005	: CC005
valve lash	: TS102	: TS102
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: 99386	: 99386
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: PAC-S90019	: PAC-S90019
interior spring	:	:
fitted load / length	: 33kg @ 35.0mm	: 33kg @ 35.0mm
max. load / lift	: 80kg @ 12.0mm	: 80kg @ 12.0mm



REMARKS :

- # - valve clearance is to be adjusted using mechanical lash caps
- please make sure that the lash cap does not touch the valve locks !
- # FOR COMPETITION APPLICATIONS ONLY. Following details must be verified:
 - the camshafts must turn smooth in the cylinderhead, provide free travel by machining where needed
 - distance between valve seal and retainer at full lift must be 0.6mm at least
 - minimum valve spring travel of 1.0mm at full lift must be provided
 - distance between valve and piston 1.0mm (pref. 1.5mm). check 5-15° before TDC on exhaust, and after TDC on intake
- # ONLY for dirt track applications and pro street use with adjustable engine management or carburetors

REMARKS :

- # if required, machine cylinder head and / or use solid shims to adjust spring load
- # check distance between valve seal and retainer to be at least 0.6mm at full lift