

1301413

sport

Bmw M42 6mm valves

I-4cyl 1.8L 16v DOHC (DTH/DTH)



	intake	exhaust
camshaft data:		
lash ramp	: hydro	hydro
duration @ 0.1mm	: 269°	269°
duration @ 1.0mm	: 225°	225°
valve lift	: 10.00mm	10.00mm
cam lift	:	
lobe angle	: 104°	108°
timing @ 1.0mm	: 8° / 37°	40° / 5°
valve lift @ TDC	: 2.00mm	1.55mm


parts setup:

cam wheels :	:	:
follower	: O.E.M.	: O.E.M.
valve lash	: O.E.M.	: O.E.M.
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: O.E.M.	: O.E.M.
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: O.E.M.	: O.E.M.
interior spring	:	:

fitted load / length	: 0kg @ 37.2mm	: 0kg @ 37.2mm
max. load / lift	: 0kg @ 0.0mm	: 0kg @ 0.0mm

REMARKS :

please check your valve stem diameter before ordering valve spring kit!

**REMARKS :**

- # - steel billet camshafts
- gundrilled for weight reduction
- for engines with 6mm valve stems (from 2000)
- # ECU reprogramming required