

1322825

tarmac rally - race

Citroën TU5JP4 110hp

I-4cyl 1.6L 16v DOHC (DTH/DTH)

**intake****exhaust****camshaft data:**

lash ramp	: 0.20mm	0.20mm
duration @ 0.1mm	: 297°	286°
duration @ 1.0mm	: 266°	257°
valve lift	: 12.55mm	12.00mm
cam lift	:	
lobe angle	: 105°	105°
timing @ 1.0mm	: 28° / 58°	54° / 23°
valve lift @ TDC	: 4.50mm	3.95mm

parts setup:

cam wheels :	CTPE001	CTPE001
follower	CC018	CC018
valve lash	TS101	TS101
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	99311/s	99311/s
lower retainer	: O.E.M.	: O.E.M.
exterior spring	PAC-S90015	PAC-S90015
interior spring		

fitted load / length	: 30kg @ 38.0mm	: 30kg @ 38.0mm
max. load / lift	: 79kg @ 13.0mm	: 79kg @ 13.0mm

REMARKS :

Double springs PAC-D99864 or PAC-D19864 (gold) can also be used with retainer 99311/S (machining around the valve guide is required). See valve setup section for fitting details. Recommended for applications above 8.500rpm


Inlet Valves:

9249005 d6.00 // D31.3 // L103.7

Exhaust Valves:

9249006 d6.00 // D26.0 // L104.2 Oversize

9249016 d6.00 // D24.5 // L104.2

**REMARKS :**

- # FOR COMPETITION APPLICATIONS ONLY. Following details must be verified:
 - the camshafts must turn smooth in the cylinderhead, provide free travel by machining where needed
 - distance between valve seal and retainer at full lift must be 0.6mm at least
 - minimum valve spring travel of 1.0mm at full lift must be provided
 - distance between valve and piston 1.0mm (pref. 1.5mm). check 5-15° before TDC on exhaust, and after TDC on intake
- # - valve clearance is to be adjusted using mechanical lash caps
- # - please make sure that the lash cap does not touch the valve locks !
- # ONLY for use in competition engines with independent engine management (throttle position sensor) or carburettors

