

1901657

full race

Fiat 182 A4.000 103hp

I-4cyl 1.6L 16v DOHC (DTH/DTH)




camshaft data:

	intake	exhaust
lash ramp	: 0.25mm	0.25mm
duration @ 0.1mm	: 327°	327°
duration @ 1.0mm	: 284°	284°
valve lift	: 12.40mm	12.40mm
cam lift	:	
lobe angle	: 105°	105°
timing @ 1.0mm	: 38° / 66°	68° / 36°
valve lift @ TDC	: 5.90mm	5.70mm

parts setup:

cam wheels :	:	:
follower	: CC002	: CC002
valve lash	: TS102	: TS102
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: O.E.M.	: O.E.M.
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: PAC-E92009	: PAC-E92009
interior spring	: PAC-I92009	: PAC-I92009
fitted load / length	: 30kg @ 35.0mm	: 30kg @ 35.0mm
max. load / lift	: 98kg @ 14.0mm	: 98kg @ 14.0mm

REMARKS :



REMARKS :

- # FOR COMPETITION APPLICATIONS ONLY. Following details must be verified:
 - the camshafts must turn smooth in the cylinderhead, provide free travel by machining where needed
 - distance between valve seal and retainer at full lift must be 0.6mm at least
 - minimum valve spring travel of 1.0mm at full lift must be provided
 - distance between valve and piston 1.0mm (pref. 1.5mm). check 5-15° before TDC on exhaust, and after TDC on intake
- # ONLY for use in competition engines with independent engine management (throttle position sensor) or carburetors