

2290308

tarmac rally - race


Ford Zeta 1.8 - 2.0L, mech (blacktop)

I-4cyl 2.0L 16v DOHC (DTs/DTs)



	intake	exhaust
camshaft data:		
lash ramp	: 0.25mm	0.25mm
duration @ 0.1mm	: 285°	277°
duration @ 1.0mm	: 252°	243°
valve lift	: 12.50mm	12.00mm
cam lift	: 12.50mm	12.00mm
lobe angle	: 105°	105°
timing @ 1.0mm	: 21° / 51°	47° / 16°
valve lift @ TDC	: 3.80mm	3.30mm
parts setup:		
cam wheels :	:	:
follower	: O.E.M.	: O.E.M.
valve lash	: O.E.M.	: O.E.M.
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: 99312/H	: 99312/H
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: PAC-E99862	: PAC-E99862
interior spring		
fitted load / length	: 29kg @ 35.0mm	: 29kg @ 35.0mm
max. load / lift	: 80kg @ 12.0mm	: 80kg @ 12.0mm

REMARKS :



REMARKS :

- # for 2nd generation engines with mechanic tappets 30mm / shim 27.5mm on top, tripple groove valves and conical valve springs (from '98)
- # FOR COMPETITION APPLICATIONS ONLY. Following details must be verified:
 - the camshafts must turn smooth in the cylinderhead, provide free travel by machining where needed
 - distance between valve seal and retainer at full lift must be 0.6mm at least
 - minimum valve spring travel of 1.0mm at full lift must be provided
 - distance between valve and piston 1.0mm (pref. 1.5mm). check 5-15° before TDC on exhaust, and after TDC on intake
- # ONLY for use in competition engines with independent engine management (throttle position sensor) or carburettors