

2501116

full race

Honda D16A6


I-4cyl 1.6L 16v SOHC



	intake	exhaust
camshaft data:		
lash ramp	: 0.30mm	0.33mm
duration @ 0.1mm	: 310°	298°
duration @ 1.0mm	: 268°	260°
valve lift	: 12.00mm	11.75mm
cam lift	: 7.40mm	6.20mm
lobe angle	: 104°	104°
timing @ 1.0mm	: 30° / 58°	54° / 26°
valve lift @ TDC	: 4.75mm	4.30mm
parts setup:		
cam wheels :	:	:
follower	: O.E.M.	: O.E.M.
valve lash	: O.E.M.	: O.E.M.
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: 99351/s	: 99352/s
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: PAC-S90015	: PAC-S90015
interior spring		
fitted load / length	: 28kg @ 38.5mm	: 28kg @ 38.5mm
max. load / lift	: 79kg @ 13.5mm	: 79kg @ 13.5mm

REMARKS :

- # The original valve springs can handle a high valve lift, however they are very weak and cannot exceed the original rpm limit. For this reason, upgrading to Cat Cams springs is advised
- # if required, use extra shims to increase spring load
- # double spring PAC-D19864 can also be used on retainers 99351 and 99352(requires dedicated lower retainer and valve seal)



REMARKS :

- # These camshafts do not have a fuel lobe. To use these camshafts in carburettor engines (like the D14A1), an electrical fuel pump should be used
- # FOR COMPETITION APPLICATIONS ONLY. Following details must be verified:
 - the camshafts must turn smooth in the cylinderhead, provide free travel by machining where needed
 - distance between valve seal and retainer at full lift must be 0.6mm at least
 - minimum valve spring travel of 1.0mm at full lift must be provided
 - distance between valve and piston 1.0mm (pref. 1.5mm). check 5-15° before TDC on exhaust, and after TDC on intake
- # ONLY for use in competition engines with independent engine management (throttle position sensor) or carburettors