

2504005

full race

Honda L15B1 130hp

I-4cyl 1.5L 16v DOHC (RPR/RPR)



camshaft data:


	intake	exhaust
lash ramp	: 0.35mm	: 0.35mm
duration @ 0.1mm	: 324° (254)	: 284° (284)
duration @ 1.0mm	: 256° (209)	: 244° (244)
valve lift	: 12.50mm (9.75)	: 12.00mm (12.00)
cam lift	: 6.90mm (5.45)	: 6.80mm (5.80)
lobe angle	: 148° (135)	: 112° (112)
timing @ 1.0mm	: -20° / 96°	: 54° / 10°
valve lift @ TDC	: 0.60mm (0.35)	: 2.35mm (2.35)

parts setup:

cam wheels :	:	:
follower :	O.E.M.	O.E.M.
valve lash :	O.E.M.	O.E.M.
valve :	O.E.M.	O.E.M.
valve locks :	O.E.M.	O.E.M.
upper retainer :	99595/s	99595/s
lower retainer :	99596/O	99596/O
exterior spring :	PAC-E99865	PAC-E99865
interior spring :	PAC-I99865	PAC-I99865

fitted load / length	: 30kg @ 31.0mm	: 34kg @ 30.0mm
max. load / lift	: 72kg @ 12.0mm	: 74kg @ 11.5mm

REMARKS :



REMARKS :

- # Camshafts are not compatible with L15B7 turbo engine.
- # ONLY for use in competition engines with independent engine management (throttle position sensor) or carburetors
- # Check workshop manual for advised valve clearance.