

2701801

sport

Hyundai G4GF Beta 1

I-4cyl 2.0L 16v DOHC (DTH/DTH)


**intake****exhaust****camshaft data:**

lash ramp	: hydro	hydro
duration @ 0.1mm	: 254°	247°
duration @ 1.0mm	: 219°	211°
valve lift	: 10.15mm	10.00mm
cam lift	:	
lobe angle	: 110°	110°
timing @ 1.0mm	: -1° / 40°	36° / -5°
valve lift @ TDC	: 0.95mm	0.60mm

parts setup:

cam wheels :	:	:
follower	: O.E.M.	: O.E.M.
valve lash	: O.E.M.	: O.E.M.
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: O.E.M.	: O.E.M.
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: O.E.M.	: O.E.M.
interior spring	:	:

fitted load / length	: 25kg @ 37.2mm	: 27kg @ 36.5mm
max. load / lift	: 60kg @ 10.0mm	: 60kg @ 9.5mm

REMARKS :**REMARKS :**

- # Only for use in early type G4GF engines with hydraulic cam followers.
Non cvvt engine.
- # ECU reprogramming required