

3702301

full race

Mazda B6 NB (solid cam followers)

I-4cyl 1.6L 16v DOHC (DTs/DTs)


**intake****exhaust****camshaft data:**

lash ramp	: 0.25mm	0.25mm
duration @ 0.1mm	: 302°	294°
duration @ 1.0mm	: 256°	248°
valve lift	: 11.20mm	10.80mm
cam lift	: 11.20mm	10.80mm
lobe angle	: 106°	106°
timing @ 1.0mm	: 22° / 54°	50° / 18°
valve lift @ TDC	: 3.55mm	3.15mm

parts setup:

cam wheels :	: CTMA023	: CTMA023
follower	: O.E.M.	: O.E.M.
valve lash	: O.E.M.	: O.E.M.
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: O.E.M.	: O.E.M.
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: PAC-S90015	: PAC-S90015
interior spring		

fitted load / length	: 25kg @ 39.5mm	: 23kg @ 39.5mm
max. load / lift	: 73kg @ 13.0mm	: 73kg @ 13.0mm

REMARKS :**REMARKS :**

- # For later B6 engine (MX5 NB) with 30mm solid cam followers (27mm shims on top)
- # FOR COMPETITION APPLICATIONS ONLY. Following details must be verified:
 - the camshafts must turn smooth in the cylinderhead, provide free travel by machining where needed
 - distance between valve seal and retainer at full lift must be 0.6mm at least
 - minimum valve spring travel of 1.0mm at full lift must be provided
 - distance between valve and piston 1.0mm (pref. 1.5mm). check 5-15° before TDC on exhaust, and after TDC on intake
- # ONLY for use in competition engines with independent engine management (throttle position sensor) or carburetors