

4341521


sport

Mitsubishi 4G63 evo 1-2-3

I-4cyl 2.0L 16v DOHC (RPRH/RPRH)



	intake	exhaust
camshaft data:		
lash ramp	: hydro	hydro
duration @ 0.1mm	: 252°	243°
duration @ 1.0mm	: 208°	200°
valve lift	: 10.50mm	10.00mm
cam lift	: 6.05mm	5.80mm
lobe angle	: 110°	110°
timing @ 1.0mm	: -7° / 35°	30° / -10°
valve lift @ TDC	: 0.50mm	0.35mm
parts setup:		
cam wheels :	:	:
follower :	O.E.M.	O.E.M.
valve lash :	O.E.M.	O.E.M.
valve :	O.E.M.	O.E.M.
valve locks :	O.E.M.	O.E.M.
upper retainer :	O.E.M.	O.E.M.
lower retainer :	O.E.M.	O.E.M.
exterior spring :	O.E.M.	O.E.M.
interior spring :	O.E.M.	O.E.M.
fitted load / length	: 28kg @ 39.5mm	: 32kg @ 38.5mm
max. load / lift	: 82kg @ 11.5mm	: 82kg @ 10.5mm



REMARKS :

- # **"type 1"** steel billet camshafts for Mitsubishi 4G63 DOHC engines (Lancer evo 1-2-3):
 - engine fitted left / gearbox right (driver's point of view)
 - ignition drive on intake camshaft with **M8** bolt

REMARKS :