

4901658

tarmac rally - race

Citroën EW10J4 135hp

I-4cyl 2.0L 16v DOHC (DTH/DTH)


**intake****exhaust****camshaft data:**

lash ramp	: 0.20mm	0.20mm
duration @ 0.1mm	: 282°	273°
duration @ 1.0mm	: 253°	242°
valve lift	: 11.75mm	11.00mm
cam lift	:	
lobe angle	: 105°	105°
timing @ 1.0mm	: 22° / 51°	46° / 16°
valve lift @ TDC	: 3.75mm	3.05mm

parts setup:

cam wheels :	CTPE002	CTPE002
follower	CC018	CC018
valve lash	TS102	TS102
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	99410/s	99410/s
lower retainer	: O.E.M.	: O.E.M.
exterior spring	PAC-E99862	PAC-E99862
interior spring		

fitted load / length	: 27kg @ 35.5mm	: 27kg @ 35.5mm
max. load / lift	: 80kg @ 12.5mm	: 80kg @ 12.5mm

REMARKS :**REMARKS :**

- # - cast iron camshafts
- trigger on exhaust camshaft
- # FOR COMPETITION APPLICATIONS ONLY. Following details must be verified:
 - the camshafts must turn smooth in the cylinderhead, provide free travel by machining where needed
 - distance between valve seal and retainer at full lift must be 0.6mm at least
 - minimum valve spring travel of 1.0mm at full lift must be provided
 - distance between valve and piston 1.0mm (pref. 1.5mm). check 5-15° before TDC on exhaust, and after TDC on intake
- # - valve clearance is to be adjusted using mechanical lash caps
- please make sure that the lash cap does not touch the valve locks !
- # ONLY for use in competition engines with independent engine management (throttle position sensor) or carburetors