

4902827

tarmac rally - race

Citroën EW10J4S 180hp

I-4cyl 2.0L 16v DOHC (DTH/DTH)



intake

exhaust

camshaft data:

lash ramp : hydro
duration @ 0.1mm : 285°
duration @ 1.0mm : 241°
valve lift : 11.50mm
cam lift :
lobe angle : 104°
timing @ 1.0mm : 16° / 45°
valve lift @ TDC : 2.95mm

hydro
285°
241°
11.50mm

104°
44° / 17°
2.95mm


parts setup:

cam wheels :	: CTPE002	: CTPE002
follower	: O.E.M.	: O.E.M.
valve lash	: O.E.M.	: O.E.M.
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: 99410/s	: 99410/s
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: PAC-S90015	: PAC-S90015
interior spring		

fitted load / length	: 30kg @ 38.0mm	: 30kg @ 38.0mm
max. load / lift	: 79kg @ 13.0mm	: 79kg @ 13.0mm

REMARKS :

#		
# Inlet Valves:		#
9249003 d6.00 // D35.0 // L106.1		#
Exhaust Valves:		#
9249004 d6.00 // D31.0 // L102.9		



REMARKS :

- # The intake camshaft is similar to the exhaust camshaft to fit two adjustable (non VVT) pulleys. When ordering, replace '4901xxx' by '4902xxx' (eg: 4901902 > 4902902)
- # FOR COMPETITION APPLICATIONS ONLY. Following details must be verified:
 - the camshafts must turn smooth in the cylinderhead, provide free travel by machining where needed
 - distance between valve seal and retainer at full lift must be 0.6mm at least
 - minimum valve spring travel of 1.0mm at full lift must be provided
 - distance between valve and piston 1.0mm (pref. 1.5mm). check 5-15° before TDC on exhaust, and after TDC on intake
- # ONLY for use in competition engines with independent engine management (throttle position sensor) or carburetors
- # evolution of 4902807