

5801413

full race

Rover K series


**intake****exhaust****camshaft data:**

lash ramp	: 0.15mm	0.15mm
duration @ 0.1mm	: 295°	287°
duration @ 1.0mm	: 263°	255°
valve lift	: 12.50mm	12.00mm
cam lift	:	
lobe angle	: 105°	105°
timing @ 1.0mm	: 27° / 56°	53° / 22°
valve lift @ TDC	: 4.60mm	4.10mm

parts setup:

cam wheels :	:	:
follower	: CC002	: CC002
valve lash	: TS101	: TS101
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: O.E.M.	: O.E.M.
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: PAC-S90015	: PAC-S90015
interior spring	:	:

fitted load / length	: 31kg @ 37.5mm	: 31kg @ 37.5mm
max. load / lift	: 79kg @ 12.5mm	: 79kg @ 12.5mm

REMARKS :**REMARKS :**

- # FOR COMPETITION APPLICATIONS ONLY. Following details must be verified:
 - the camshafts must turn smooth in the cylinderhead, provide free travel by machining where needed
 - distance between valve seal and retainer at full lift must be 0.6mm at least
 - minimum valve spring travel of 1.0mm at full lift must be provided
 - distance between valve and piston 1.0mm (pref. 1.5mm). check 5-15° before TDC on exhaust, and after TDC on intake
- # ONLY for use in competition engines with independent engine management (throttle position sensor) or carburetors