

6401353

sport

Subaru

B-4cyl 2.5L 16v DOHC (DTs/DTs)




	intake	exhaust
camshaft data:		
lash ramp	: 0.35mm	0.45mm
duration @ 0.1mm	: 251°	251°
duration @ 1.0mm	: 215°	208°
valve lift	: 8.90mm	8.80mm
cam lift	: 8.90mm	8.80mm
lobe angle	: 112°	112°
timing @ 1.0mm	: -5° / 40°	36° / -8°
valve lift @ TDC	: 0.85mm	0.85mm

parts setup:

cam wheels :	:	:
follower	: O.E.M.	: O.E.M.
valve lash	: O.E.M.	: O.E.M.
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: O.E.M.	: O.E.M.
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: O.E.M.	: O.E.M.
interior spring	:	:

fitted load / length	: 16kg @ 42.0mm	: 16kg @ 42.0mm
max. load / lift	: 55kg @ 11.0mm	: 55kg @ 11.0mm

REMARKS :**REMARKS :**

- # - bearing diameters: 32.0mm - 28.0mm - 28.0mm
- cam base diameter: 34.0mm
- cam followers: mechanic tappet 33mm with 30mm shim
- # Sport camshaft for Subaru Impreza 2.5L 16v Turbo (1998 US model)