

7103119


tarmac rally - race

Toyota 2T-G Celica 1600 GT 99hp

I-4cyl 1.6L 8v DOHC



	intake	exhaust
camshaft data:		
lash ramp	: 0.20mm	0.20mm
duration @ 0.1mm	: 289°	289°
duration @ 1.0mm	: 262°	262°
valve lift	: 12.50mm	12.50mm
cam lift	: 12.50mm	12.50mm
lobe angle	: 106°	106°
timing @ 1.0mm	: 25° / 57°	57° / 25°
valve lift @ TDC	: 4.45mm	4.45mm
parts setup:		
cam wheels :	:	:
follower	: O.E.M.	: O.E.M.
valve lash	: O.E.M.	: O.E.M.
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	: O.E.M.	: O.E.M.
lower retainer	: O.E.M.	: O.E.M.
exterior spring	: PAC-E99859	: PAC-E99859
interior spring	: PAC-I99859	: PAC-I99859
fitted load / length	: 34kg @ 35.5mm	: 34kg @ 35.5mm
max. load / lift	: 110kg @ 14.0mm	: 110kg @ 14.0mm



REMARKS :

- # replace STD spring by double spring [ref. 99859] on STD spring retainers. shim spring to fitted length of 34.5-35.5mm
- # ONLY for use in competition engines with independent engine management (throttle position sensor) or carburetors

REMARKS :