

7605132

sport


Volkswagen GK, FZ, FA, GG, HH 60hp

I-4cyl 1.3L 8v SOHC (RP/RP)



	intake	exhaust
camshaft data:		
lash ramp	: 0.20mm	0.20mm
duration @ 0.1mm	: 274°	274°
duration @ 1.0mm	: 238°	238°
valve lift	: 9.20mm	9.20mm
cam lift	: 6.65mm	6.65mm
lobe angle	: 108°	108°
timing @ 1.0mm	: 13° / 45°	49° / 9°
valve lift @ TDC	: 2.45mm	2.10mm
parts setup:		
cam wheels :	:	:
follower :	O.E.M.	O.E.M.
valve lash :	O.E.M.	O.E.M.
valve :	O.E.M.	O.E.M.
valve locks :	O.E.M.	O.E.M.
upper retainer :	O.E.M.	O.E.M.
lower retainer :	O.E.M.	O.E.M.
exterior spring :	O.E.M.	O.E.M.
interior spring :		
fitted load / length	: 23kg @ 30.5mm	: 23kg @ 30.5mm
max. load / lift	: 52kg @ 10.0mm	: 52kg @ 10.0mm

REMARKS :



REMARKS :

- # Distance between valve and piston should be 1.0mm at least:
 - check 5-15° after TDC on intake
 - check 5-15° before TDC on exhaust
- Machine pistons if required. Wrong installation can cause severe engine damage!