

7901412

tarmac rally - race

Volvo B230 B19 - B21 - B23 - B230

I-4cyl 2.3L 8v SOHC (DTs/DTs)



intake

exhaust

camshaft data:


lash ramp	: 0.25mm	0.25mm
duration @ 0.1mm	: 305°	303°
duration @ 1.0mm	: 266°	262°
valve lift	: 13.50mm	12.75mm
cam lift	:	
lobe angle	: 106°	106°
timing @ 1.0mm	: 27° / 59°	57° / 25°
valve lift @ TDC	: 4.95mm	4.45mm

parts setup:

cam wheels :	CTV0021	CTV0021
follower	CC009	CC009
valve lash	TS103	TS103
valve	: O.E.M.	: O.E.M.
valve locks	: O.E.M.	: O.E.M.
upper retainer	99326	99326
lower retainer	not available	not available
exterior spring	PAC-E95009	PAC-E95009
interior spring	PAC-I95009	PAC-I95009
fitted load / length	: 36kg @ 34.0mm	: 36kg @ 34.0mm
max. load / lift	: 113kg @ 14.0mm	: 113kg @ 14.0mm

REMARKS :

- # replace OEM lower retainer to obtain a correct installation / fitted length (currently not available)



REMARKS :

- # Volvo has used many different camshaft specifications. Please indicate STD cam base diameter and cam height when ordering sports camshafts. Depending on the engine version and application, extra modifications may be required.
- # FOR COMPETITION APPLICATIONS ONLY. Following details must be verified:
 - the camshafts must turn smooth in the cylinderhead, provide free travel by machining where needed
 - distance between valve seal and retainer at full lift must be 0.6mm at least
 - minimum valve spring travel of 1.0mm at full lift must be provided
 - distance between valve and piston 1.0mm (pref. 1.5mm). check 5-15° before TDC on exhaust, and after TDC on intake
- # ONLY for use in competition engines with independent engine management (throttle position sensor) or carburetors